

VIAVI

Network & Service Companion (NSC-200)

Enterprise Ethernet Test up to 10 Gbps

Empower techs with the simplest, most comprehensive, fastest (one-minute) service activation test and troubleshooting solution.

The NSC-200 is a test solution for Ethernet, Enterprise and Data Center Networks. It combines active Ethernet and WiFi testing capabilities enabling service activation and troubleshooting tests on all network layers up to 10G.

- Simplify the Ethernet turn-up and troubleshooting process by enabling Ethernet tests on network Layers 2, 3, and 4.
- Identify and prevent customer affecting throughput issues by running active throughput tests up to 10 Gbps (Speedtest, TrueSpeed RFC6349, iPerf).
- Validate business services as standalone unit, or as remote loopback device when combined with the T-BERD/MTS-5800 for Y.1564 and RFC2544 tests.
- Optimize WiFi coverage and performance; get network improvement recommendations when performance is below expectation.
- Perform 24/7 monitoring sessions for long-term, root cause failure analysis and SLA monitoring.



Benefits

- Support of Fiber, Ethernet and WiFi in one solution – up to 10G
- Flexible multi-tool for enterprise and fixed-line/mobile fronthaul service installation, performance measurements and troubleshooting
- Drive compliance of both direct and contracted staff with centralized, cloud-based workflow and result management
- Remote control for leave-behind use case enables long-term testing and failure analysis
- Service activation up to 10 Gbps, test and performance management (L2/L3 loopback up to 10G, TWAMP reflector)
- Centralized test system (VIAVI Fusion) leveraging NSCs as remote controlled test agents

Features

- Ethernet test interfaces up to 10G
- Ethernet testing up to Layer 4 (TCP/UDP) and up to 10 Gbps
- WiFi 3x3 tests and WiFi Expert up to WiFi 6
- StrataSync and Mobile Tech app support
- Job Manager



2019 Broadband Technology Review –
4.0 Diamond Award Winner



2022 Broadband Technology Review –
4.0 Diamond Award Winner



2020 Lightwave Innovation Award 4.5 Winner

Specifications

GPON (Optional)		
ONU/ONT	VIAVI GPON SFP	
Interface	SC/APC	
Standard	G.984.2 GPON compliant	
	G.988 OMCI compliant	
Upstream (1310 nm) Tx Signal Power Range	0.5 dBm to 5.0 dBm	
Downstream (1490 nm) Rx Signal Power Range	-28.0 dBm to -8.0 dBm	
Test Results	PON Activation State, Power Level values from the SFP, PON ID, ODN Class – according to ITU-T G.984 and G.988 standards	
XGSPON (Optional)		
ONU/ONT	VIAVI XGSPON SFP	
Interface	SC/APC	
Standard	G.9807.1 XGSPON compliant	
	G.988 OMCI compliant	
Upstream (1270 nm) Tx Signal Power Range	4.0 dBm to 9.0 dBm	
Downstream (1577 nm) Rx Signal Power Range	-28.0 dBm to -9.0 dBm	
Test Results	PON Activation State, Power Level values from the SFP, PON ID, ODN Class – according to ITU-T G.9807 and G.988 standards	
Ethernet (Optional)		
Standard	IEEE 802.3	
	10M, 100M, 1G, 2.5G, 5G, and 10G Ethernet	
Test Results	Ethernet Frames, IP Connectivity, Ping, Traceroute, Web Connectivity, Speed Test up to 10 Gbps	
TWAMP Reflector (Optional)	10M, 100M, and 1G Ethernet	
	TWAMP Light Reflector support	
Port/L2/L3 Loopback (Optional)	10M, 100M, 1G, and 10G Ethernet	
	Port Loopback and Source specific VIAVI Loopback support	
WiFi (Optional)		
Test Results	WiFi Expert (Passive Mode)	Up to WiFi 6 (802.11 a/b/g/n/ac/ax) <ul style="list-style-type: none"> Signal strength (RSSI), Channel, Standard, Width, Channel Noise, Total Airtime, Noise Airtime, Estimated Throughput, Recommendations
	OneCheck WiFi (Connected Mode)	Up to WiFi 5 3x3 (802.11 a/b/g/n/ac) <ul style="list-style-type: none"> Signal strength (RSSI), Standard, Width, Max Router PHY Rate, IP/Web connectivity, Throughput Tests
Throughput / Performance Test (Optional)		
TCP Throughput Test	VIAVI SpeedCheck Ookla Speedtest VIAVI TrueSpeed (RFC-6349) iPerf	
Performance	10 Gbps for SpeedCheck, Ookla Speedtest, TrueSpeed, iPerf	
Test Results	Delay, Upstream and Downstream Bit Rates	

User Interface	
Communication Interface	Bluetooth v5.0
Smart Device Support (recommendation)	Mobile Tech app
	Android 8 or newer
	iOS 12 or newer
VIAVI Instrument Support	ONX-580, ONX-CATV
General	
Size	116 x 190 x 52 mm (4.6 x 7.5 x 2.0 in)
Weight	0.8 kg (1.7 lb)
Operating Temperature Range	Non-Charging: -10°C to 50°C
	Battery Charging: 0°C to 40°C
Storage Temperature Range	-20°C to 60°C
Operating Humidity Range	10% to 90% RH, non-condensing
Operating Altitude	4000 m max
DC Input Power	15V @ 3A, USB-C Power Delivery (PD)
Battery	32 W/hr Li-Ion rechargeable battery
	Field replaceable
Battery Life	1-week typical usage for installation technicians
Charge Port	USB-C
USB Host Port	USB-A (USB 3.0)

Ordering Information

Standard Packages		
PON Package	NSC200-GPON-BASE	GPON
	NSC200-GPON-PLUS	GPON, Ethernet, SpeedCheck 1G, Speedtest 1G
	NSC200-GPON-PRO	GPON, Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G
	NSC200-XGSPON-BASE	XGSPON
	NSC200-XGSPON-PLUS	XGSPON, Ethernet, SpeedCheck 1G, Speedtest 1G
	NSC200-XGSPON-PRO	XGSPON, Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G
	NSC200-GPON-XGSPON-BASE	GPON, XGSPON
	NSC200-GPON-XGSPON-PLUS	GPON, XGSPON, Ethernet, SpeedCheck 1G, Speedtest 1G
	NSC200-GPON-XGSPON-PRO	GPON, XGSPON, Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G
Home Package	NSC200-HOME-PLUS	Ethernet, SpeedCheck 1G, Speedtest 1G
	NSC200-HOME-PRO	Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G
Enterprise	NSC200-ENTERPRISE-PLUS	Ethernet, TrueSpeed 1G
	NSC200-ENTERPRISE-PRO	Ethernet, WiFi, TrueSpeed 1G
Loopback	NSC200-LOOPBACK-BASE	Ethernet Loopback 1G
	NSC200-LOOPBACK-PLUS	Ethernet Loopback 10G
Platinum	NSC200-PLATINUM-1G	XGSPON, Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G, TrueSpeed 1G, Loopback 1G, TWAMP
	NSC200-PLATINUM-10G	XGSPON, Ethernet, WiFi, SpeedCheck 10G, Speedtest 10G, TrueSpeed 10G, Loopback 10G, TWAMP
Options		
Test Applications	NSC-OC-GPON	NSC OneCheck GPON
	NSC-OC-XGSPON	NSC OneCheck XGSPON
	NSC-OC-ETHERNET	NSC OneCheck Ethernet
	NSC-OC-WIFI	NSC OneCheck WiFi
	NSC-WIFI-EXPERT	NSC WiFi Expert
Speed Tests	NSC-SPEEDCHECK-1G	NSC SpeedCheck over 1GE port up to 1Gbps
	NSC-SPEEDCHECK-2G	NSC SpeedCheck over 2.5/5/10GE port up to 2Gbps
	NSC-SPEEDCHECK-5G	NSC SpeedCheck over 2.5/5/10GE port up to 5Gbps
	NSC-SPEEDCHECK-10G	NSC SpeedCheck over 2.5/5/10GE port up to 10Gbps
	NSC-SPEEDTEST-1G	NSC Ookla Speedtest over 1GE port up to 1Gbps
	NSC-SPEEDTEST-2G	NSC Ookla Speedtest over 1+1/2.5/5/10GE ports up to 2Gbps
	NSC-SPEEDTEST-5G	NSC Ookla Speedtest over 2.5/5/10GE port up to 5Gbps
	NSC-SPEEDTEST-10G	NSC Ookla Speedtest over 2.5/5/10GE port up to 10Gbps
	NSC-TRUESPEED-1G	NSC TrueSpeed (RFC-6349) over 1GE port up to 1Gbps
	NSC-TRUESPEED-2G	NSC TrueSpeed (RFC-6349) over 2.5/5/10GE port up to 2Gbps
	NSC-TRUESPEED-5G	NSC TrueSpeed (RFC-6349) over 2.5/5/10GE port up to 5Gbps
	NSC-TRUESPEED-10G	NSC TrueSpeed (RFC-6349) over 2.5/5/10GE port up to 10Gbps
	NSC-IPERF-1G	NSC iPerf Test over 1GE port up to 1Gbps
	NSC-IPERF-2G	NSC iPerf Test over 2.5/5/10GE port up to 2Gbps
NSC-IPERF-5G	NSC iPerf Test over 2.5/5/10GE port up to 5Gbps	
NSC-IPERF-10G	NSC iPerf Test over 2.5/5/10GE port up to 10Gbps	

Ordering Information continued

Options continued		
Enterprise	NSC-LOOPBACK-1G	NSC L2/L3 1G Loopback
	NSC-LOOPBACK-10G	NSC L2/L3 10G Loopback
	NSC-FUSION-CLIENT	NSC Fusion Client
	NSC-TWAMP-REFLECTOR	NSC TWAMP Reflector
	NSC-OPTICAL-ETHERNET	NSC Optical Ethernet
SFP	NSC-SFP-ELEC-1G	NSC 1G Electrical Ethernet SFP
	NSC-SFP-ELEC-AUTO-10G	NSC 2.5G, 5G and 10G Autoneg Electrical Ethernet SFP+
	NSC-SFP-ELEC-1-2.5-5-10G	NSC 1G, 2.5G, 5G and 10G Electrical Ethernet SFP+
	NSC-SFP-850-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 850 nm SR
	NSC-SFP-1310-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 1310 nm LR
	NSC-SFP-1550-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 1550 nm ER
	NSC-SFP-GPON	NSC GPON SFP
	NSC-SFP-XGSPON	NSC XGSPON SFP+
Optional Accessory		
	NSC-CAR-CHARGER	Car Charger with Cable
Replacement Parts		
	NSC-BATTERY	NSC Battery
	NSC-CHARGER	NSC Charger with Cable
	NSC-STRAP	NSC Hand Strap
	NSC-CASE	NSC Carrying Case
	NSC-ETHERNET-ADAPTER	Ethernet Cat6a M-F Adapter Cable
	NSC-ETHERNET-CABLE	Ethernet Cat6a M-M Patch Cable



Contact Us **+1 844 GO VIAMI**
(+1 844 468 4284)

To reach the VIAMI office nearest you,
visit viavisolutions.com/contact

© 2023 VIAMI Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
Patented as described at
viavisolutions.com/patents
nsc200-ethernet-ds-xpf-nse-ae
30193263 904 0223